

PA System

HUKE Electronics Co.,Ltd

PA System

HUKE Electronics Co.,Ltd

Founded in 1999, HUKE Electronics Co.,Ltd is located in Ningbo city China, where it is very convenient to ship by sea. We specialize in professional audio manufacturing, such as passive, active speaker cabinet, mixer, stand, cable, DI BOX and so on. Experienced team with latest technology and equipment for example Clío, LMS always meet customers' needs.

We are a medium-scale factory, being serious and honest for long-term cooperation partnership is our business pursuit. We take quality and promptly delivery as the Life, assuring each qualified component to be used in the complete product, 100% inspection before shipment with two years warranty after sale.

With years of effort and development, HUKE has achieved good reputation in pro audio industry worldwide. We keep on innovating, HUKE will be your reliable OEM & ODM partner here. Thanks and enjoy your stay with us.

Add: HongTang Industrial Zone A,
HongTang Town, Ningbo China
Tel: 0086-574-86121429
Fax: 0086-574-86121429
Email: huke@hukeelectronics.com
Http://www.hukeelectronics.com

Professional Speaker Cabinet

Professional Speaker Cabinet

PU Serie

Moulded Speaker Cabinet



PU-15 & PU-15A

Specifications:

Model:	PU-15	PU-15AU
System type:	15" 2 Way passive	15" 2 Way active
Power handling:	250W, 500W PEAK	250W, 500W PEAK
LF woofer:	15" with 2.5" kapton voice coil 50 OZ magnet	15" with 2.5" kapton voice coil 50 OZ magnet
HF driver:	1.75" Titanium	1.75" Titanium
Frequency response:	40Hz-18KHz	40Hz-18KHz
Impedance:	8 Ohm	4 Ohm
Sensitivity:	98dB	98 dB
Amplifier module:		250W RMS Digital AMP
Functions:		Mp3 player, DSP, SD card input, Bluetooth, FM radio, 5 Band EQ, Remote controller
Connectors:	2*Speakon	Dual RCA line & XLR MIC input, XLR & 1/4JACK Line output
Dimension(W*L*H):	48.5*42*74CM	48.5*42*74CM
Weight:	19KGS	21KGS

PG Serie

Moulded Speaker Cabinet



PG-15 & PG-15AU

Specifications:

Model:	PG-15	PG-15AU
System type:	15" 2 Way passive	15" 2 Way active
Power handling:	250W, 500W PEAK	200W, 400W PEAK
LF woofer:	15" with 2.5" kapton voice coil 50 OZ magnet	15" with 2.5" kapton voice coil 50 OZ magnet
HF driver:	1.75" Titanium	1.75" Titanium
Frequency response:	40Hz-18KHz	40Hz-18KHz
Impedance:	8 Ohm	4 Ohm
Sensitivity:	97dB	97 dB
Amplifier module:		200W RMS, Analog Mp3 player, SD card input, FM radio, Bluetooth, Remote controller
Functions:		Dual RCA line & XLR MIC input, XLR & 1/4JACK Line output,
Connectors:	2*Speakon	
Dimension(W*L*H):	48.5*40*74CM	48.5*40*74CM
Weight:	18KGS	20KGS

Professional Speaker Cabinet

Professional Speaker Cabinet

PW Serie

Moulded Speaker Cabinet



PW-15 & PW-15A

Specifications:

	PW-15	PW-15AU
Model:	PW-15	PW-15AU
System type:	15" 2 Way passive	15" 2 Way active
Power handling:	250W,500W PEAK	250W,500W PEAK
LF woofer:	15"with 2.5"kapton voice coil 50 OZ magnet	15" with 2.5" kapton voice coil 50 OZ magnet
HF driver:	1.75"Titanium	1.75" Titanium
Frequency response:	40Hz-18KHz	40Hz-18KHz
Impedance:	8 Ohm	4 Ohm
Sensitivity:	98dB	98 dB
Amplifier module:		250W RMS Digital AMP
Functions:		Mp3 player,SD card input,Bluetooth, FM radio,5 Band EQ,Remote controller
Connecors:	2*Speakon	Dual RCA line & XLR MIC input, XLR & 1/4JACK Line output
Dimension(W*L*H):	48.5*42*74CM	48.5*42*74CM
Weight:	19KGS	21KGS

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

PZ Serie

Moulded Speaker Cabinet



PZ-15 & PZ-15AU

Specifications:

	PZ-15	PZ-15AU
Model:	PZ-15	PZ-15AU
System type:	15" 2 Way passive	15" 2 Way active
Power handling:	250W,500W PEAK	200W,400W PEAK
LF woofer:	15"with 2.5"kapton voice coil 50 OZ magnet	15" with 2.5" kapton voice coil 50 OZ magnet
HF driver:	1.75"Titanium	1.75" Titanium
Frequency response:	40Hz-18KHz	40Hz-18KHz
Impedance:	8 Ohm	4 Ohm
Sensitivity:	97dB	97 dB
Amplifier module:		200W RMS, Analog
Functions:		Mp3 player,SD card input, FM radio,Bluetooth, Remote controller
Connecors:	2*Speakon	Dual RCA line & XLR MIC input, XLR & 1/4JACK Line output,
Dimension(W*L*H):	48.5*42*75CM	48.5*42*75CM
Weight:	18KGS	20KGS

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

Professional Speaker Cabinet

Professional Speaker Cabinet

PX Serie

Moulded Speaker Cabinet



PX-15 & PX-15A

Specifications:

	PX-15	PX-15AU
Model:	PX-15	PX-15AU
System type:	15" 2 Way passive	15" 2 Way active
Power handling:	300W,600W PEAK	200W,500W PEAK
LF woofer:	15"with 3"kapton voice coil 60 OZ magnet	15" with 3" kapton voice coil 60 OZ magnet
HF driver:	1.75"Titanium	1.75" Titanium
Frequency response:	40Hz-18KHz	40Hz-18KHz
Impedance:	8 Ohm	4 Ohm
Sensitivity:	98dB	98 dB
Amplifier module:		200W RMS Digital AMP
Functions:		Mp3 player,SD card input,Bluetooth, FM radio,Remote controller
Connecors:	2*Speakon	Dual RCA line & XLR MIC input, XLR & 1/4JACK Line output
Dimension(W*L*H):	48*42*74CM	48*42*74CM
Weight:	19KGS	21KGS

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

PX Serie

Moulded Speaker Cabinet



PX-18 & PX-18AU

Specifications:

	PX-18	PX-18AU
Model:	PX-18	PX-18AU
System type:	18" 2 Way passive	18" 2 Way active
Power handling:	350W,700W PEAK	300W,600W PEAK
LF woofer:	18"with 3"kapton voice coil 70 OZ magnet	18" with 3" kapton voice coil 70 OZ magnet
HF driver:	1.75"Titanium	1.75" Titanium
Frequency response:	80Hz-20KHz	80Hz-20KHz
Impedance:	8 Ohm	4 Ohm
Sensitivity:	99dB	99 dB
Amplifier module:		300W RMS, Analog
Functions:		Mp3 player,SD card input, FM radio,Bluetooth,5BAND EQ, Remote controller,One supports Three in power
Connecors:	2*Speakon	Dual RCA line & XLR MIC input, XLR & 1/4JACK Line output, Dual speaker output
Dimension(W*L*H):	64*45*77CM	64*45*77CM
Weight:	24KGS	27KGS

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

Professional Speaker Cabinet

Professional Speaker Cabinet

PB Serie

Moulded Speaker Cabinet



PB-15 & PB-15A

Specifications:

Model:	PB-15	PB-15AU
System type:	15" 2 Way passive	15" 2 Way active
Power handling:	250W, 500W PEAK	250W, 500W PEAK
LF woofer:	15" with 3" kapton voice coil 60 OZ magnet	15" with 3" kapton voice coil 60 OZ magnet
HF driver:	1.75" Titanium	1.75" Titanium
Frequency response:	40Hz-18KHz	40Hz-18KHz
Impedance:	8 Ohm	4 Ohm
Sensitivity:	98dB	98 dB
Amplifier module:		250W RMS Digital AMP
Functions:		Mp3 player, SD card input, Bluetooth, FM radio, 5 Band EQ, Remote controller
Connectors:	2*Speakon	Dual RCA line & XLR MIC input, XLR & 1/4 JACK Line output
Dimension(W*L*H):	49*46*75CM	49*46*75CM
Weight:	19KGS	21KGS

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

PE Serie

Moulded Speaker Cabinet



PE-15 & PE-15AU

Specifications:

Model:	PE-15	PE-15AU
System type:	15" 2 Way passive	15" 2 Way active
Power handling:	250W, 500W PEAK	180W, 360W PEAK
LF woofer:	15" with 3" kapton voice coil 60 OZ magnet	15" with 3" kapton voice coil 60 OZ magnet
HF driver:	1.75" Titanium	1.75" Titanium
Frequency response:	40Hz-18KHz	40Hz-18KHz
Impedance:	8 Ohm	4 Ohm
Sensitivity:	98dB	98 dB
Amplifier module:		180W RMS, Analog
Functions:		Mp3 player, SD card input, FM radio, Remote controller
Connectors:	2*Speakon	Dual RCA line & XLR MIC input, XLR & 1/4 JACK Line output, Speakon output
Dimension(W*L*H):	49*42*76CM	49*42*76CM
Weight:	19KGS	21KGS

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

Professional Speaker Cabinet

Professional Speaker Cabinet

PD Serie

Moulded Speaker Cabinet



PD-12 & PD-12AU

Specifications:

Model:	PD-12	PD-12AU
System type:	12" 2 Way passive	12" 2 Way active
Power handling:	200W, 400W PEAK	200W, 400W PEAK
LF woofer:	12" with 2.5" kapton voice coil 50 OZ magnet	12" with 2.5" kapton voice coil 50 OZ magnet
HF driver:	1.35" Titanium	1.35" Titanium
Frequency response:	50Hz-18KHz	50Hz-18KHz
Impedance:	8 Ohm	4 Ohm
Sensitivity:	95dB	95 dB
Amplifier module:		200W RMS BI Amplifier
Connectors:	2*Speakon	Dual RCA line & XLR line input, Dual XLR, 1/4 Jack MIC inputs & 1/4 Jack & Canon output
Dimension(W*L*H):	46*37*64CM	46*37*64CM
Weight:	15KGS	17KGS

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

PD-15 & PD-15AU

Specifications:

Model:	PD-15	PD-15AU
System type:	15" 2 Way passive	15" 2 Way active
Power handling:	250W, 500W PEAK	250W, 500W PEAK
LF woofer:	15" with 3" kapton voice coil 60 OZ magnet	15" with 3" kapton voice coil 60 OZ magnet
HF driver:	1.75" Titanium	1.75" Titanium
Frequency response:	40Hz-18KHz	40Hz-18KHz
Impedance:	8 Ohm	4 Ohm
Sensitivity:	98dB	98 dB
Amplifier module:		250W RMS BI Amplifier
Connectors:	2*Speakon	Dual RCA line & XLR line input, Dual XLR, 1/4 Jack MIC inputs & 1/4 Jack & Canon output
Dimension(W*L*H):	50.5*46*75CM	50.5*46*75CM
Weight:	20KGS	22KGS

PD-15AU

Specifications:

Model:	PE-15AU
System type:	15" 2 Way active
Power handling:	300W, 600W PEAK
LF woofer:	15" with 3" kapton voice coil 60 OZ magnet
HF driver:	1.75" Titanium
Frequency response:	40Hz-18KHz
Impedance:	4 Ohm
Sensitivity:	98dB
Amplifier module:	300W RMS Digital
Functions:	Touch screen Mp3 player, FM radio, DSP
Connectors:	Dual RCA line & XLR line input & output, Dual Cannon MIC inputs & Speaker output
Dimension(W*L*H):	50.5*46*75CM
Weight:	21KGS



[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

Professional Speaker Cabinet

Professional Speaker Cabinet

PH Serie

Moulded Speaker Cabinet



PH-15 & PH-15A

Specifications:

	PH-15	PH-15AU
Model:	PH-15	PH-15AU
System type:	15" 2 Way passive	15" 2 Way active
Power handling:	250W,500W PEAK	250W,500W PEAK
LF woofer:	15"with 3"kapton voice coil 60 OZ magnet	15" with 3" kapton voice coil 60 OZ magnet
HF driver:	1.75"Titanium	1.75" Titanium
Frequency response:	40Hz-18KHz	40Hz-18KHz
Impedance:	8 Ohm	4 Ohm
Sensitivity:	98dB	98 dB
Amplifier module:		250W RMS, Analog
Functions:		Mp3 player,SD card input,Bluetooth, FM radio,5 Band EQ,Time & Effect, Remote controller
Connecors:	2*Speakon	Dual RCA line & XLR MIC input, XLR&1/4JACK Line output, Speakon output
Dimension(W*L*H):	50.5*48*75.5CM	50.5*48*75.5CM
Weight:	21KGS	23KGS

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

PV Serie

Moulded Speaker Cabinet



PV-15 & PV-15AU

Specifications:

	PV-15	PV-15AU
Model:	PV-15	PV-15AU
System type:	15" 2 Way passive	15" 2 Way active
Power handling:	250W,500W PEAK	250W,500W PEAK
LF woofer:	15"with 3"kapton voice coil 60 OZ magnet	15" with 3" kapton voice coil 60 OZ magnet
HF driver:	1.75"Titanium	1.75" Titanium
Frequency response:	40Hz-18KHz	40Hz-18KHz
Impedance:	8 Ohm	4 Ohm
Sensitivity:	98dB	98 dB
Amplifier module:		250W RMS,Digital AMP
Functions:		Mp3 player,SD card input,Bluetooth, FM radio,5Band EQ,Remote controller
Connecors:	2*Speakon	Dual RCA line & XLR MIC input, XLR & 1/4JACK Line output
Dimension(W*L*H):	48.5*40*74CM	48.5*40*74CM
Weight:	17KGS	19KGS

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

Professional Speaker Cabinet

Professional Speaker Cabinet

PJ Serie

Moulded Speaker Cabinet



PJ-8 & PJ-8AU

Specifications:

	PJ-8	PJ-8AU
Model:	PJ-8	PJ-8AU
System type:	8" 2 Way passive	8" 2 Way active
Power handling:	120W,240W PEAK	80W,160W PEAK
LF woofer:	8"with 1.5"kapton voice coil 30 OZ magnet	8" with 1.5" kapton voice coil 30 OZ magnet
HF driver:	1"Titanium	1" Titanium
Frequency response:	65Hz-18KHz	65Hz-18KHz
Impedance:	8 Ohm	4 Ohm
Sensitivity:	93dB	93 dB
Amplifier module:		80W RMS, Analog
Functions:		Mp3 player,SD card input, FM radio,Remote controller
Connecors:	2*Speakon	Dual RCA line & 1/4JACK MIC input &Speakon output
Dimension(W*L*H):	29*24*44CM	29*24*44CM
Weight:	9KGS	9KGS

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

PJ-10 & PJ-10AU

	PJ-10	PJ-10AU
Model:	PJ-10	PJ-10AU
System type:	10" 2 Way passive	10" 2 Way active
Power handling:	150W,300W PEAK	120W,240W PEAK
LF woofer:	10"with 2"kapton voice coil, 50 OZ magnet	10" with 2" kapton voice coil 50 OZ magnet
HF driver:	1.35"Titanium	1.35" Titanium
Frequency response:	55Hz-18KHz	55Hz-18KHz
Impedance:	8 Ohm	4 Ohm
Sensitivity:	95dB	95 dB
Amplifier module:		120W RMS Analog
Functions:		Mp3 player,SD card input,Bluetooth, FM radio,5 Band EQ,Remote controller
Connecors:	2*Speakon	Dual RCA line & XLR MIC input, XLR&1/4JACK Line output, Speakon output
Dimension(W*L*H):	38*28*54CM	38*28*54CM
Weight:	10KGS	11.5KGS

PJ-12 & PJ-12AU

	PJ-12	PJ-12AU
Model:	PJ-12	PJ-12AU
System type:	12" 2 Way passive	12" 2 Way active
Power handling:	200W,400W PEAK	150W,300W PEAK
LF woofer:	12"with 2.5"kapton voice coil, 50 OZ magnet	12" with 2.5" kapton voice coil 50 OZ magnet
HF driver:	1.35"Titanium	1.35" Titanium
Frequency response:	50Hz-18KHz	50Hz-18KHz
Impedance:	8 Ohm	4 Ohm
Sensitivity:	95dB	95 dB
Amplifier module:		150W RMS, Analog
Functions:		Mp3 player,SD card input, FM radio,Remote controller
Connecors:	2*Speakon	Dual RCA line & XLR MIC input, XLR & 1/4JACK Line output, Speakon output
Dimension(W*L*H):	42*34*63CM	42*34*63CM
Weight:	13KGS	15KGS

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

Professional Speaker Cabinet

Professional Speaker Cabinet

PJ Serie

Moulded Speaker Cabinet



PJ-15 & PJ-15AU

Model:	PJ-15	PJ-15AU
System type:	15" 2 Way passive	15" 2 Way active
Power handling:	250W, 500W PEAK	180W, 360W PEAK
LF woofer:	15" with 3" kapton voice coil, 60 OZ magnet	15" with 3" kapton voice coil, 60 OZ magnet
HF driver:	1.75" Titanium	1.75" Titanium
Frequency response:	40Hz-18KHz	40Hz-18KHz
Impedance:	8 Ohm	4 Ohm
Sensitivity:	98dB	98 dB
Amplifier module:		180W RMS ,Analog
Functions:		Mp3 player, SD card input, FM radio, Remote controller
Connectors:	2*Speakon	Dual RCA line & XLR MIC input, XLR&1/4JACK Line output, Speakon output
Dimension(W*L*H):	48.5*40*74CM	48.5*40*74CM
Weight:	18KGS	20KGS

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)



PJ-215 & PJ-215AUB

Model:	PJ-215	PJ-215AUB
System type:	Dual 15" 2 Way passive	Dual 15" 2 Way active
Power handling:	400W, 800W PEAK	350W, 700W PEAK
LF woofer:	2*15" with 3" kapton voice coil, 50 OZ magnet	2*15" with 3" kapton voice coil, 50 OZ magnet
HF driver:	1.75" Titanium	1.75" Titanium
Frequency response:	38Hz-18KHz	38Hz-18KHz
Impedance:	4 Ohm	4 Ohm
Sensitivity:	99dB	99 dB
Amplifier module:		350W RMS Analog
Functions:		Mp3 player, SD card input, Bluetooth, FM radio, 5 band EQ, Time&Effect, Wireless mics, Remote controller
Connectors:	2*Speakon	Dual RCA line & XLR Mic input, XLR&1/4JACK line output, Speakon output
Dimension(W*L*H):	48.5*40*115CM	48.5*40*115CM
Weight:	30KGS	34KGS

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

Professional Speaker Cabinet

Professional Speaker Cabinet

PM Serie

Moulded Speaker Cabinet



PM-12 & PM-12AUI

Model:	PM-12	PM-12AUI
System type:	12" 2 Way passive	12" 2 Way active
Power handling:	200W, 400W PEAK	200W, 400W PEAK
LF woofer:	12" with 2.5" kapton voice coil, 50 OZ magnet	12" with 2.5" kapton voice coil, 50 OZ magnet
HF driver:	1.35" Titanium	1.35" Titanium
Frequency response:	50Hz-18KHz	50Hz-18KHz
Impedance:	8 Ohm	4 Ohm
Sensitivity:	95dB	95 dB
Amplifier module:		200W RMS Digital
Functions:		Mp3 player, SD card input, Ipod dock, 5 band EQ, FM radio, Remote controller
Connectors:	2*Speakon	Dual RCA line & XLR line input, Dual XLR&1/4JACK MIC input, 1/4Jack MIC input, XLR output
Dimension(W*L*H):	44.5*38*64.5CM	44.5*38*64.5CM
Weight:	16.5KGS	18.5KGS

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

PM-15 & PM-15AUI

Model:	PM-15	PM-15AUI
System type:	15" 2 Way passive	15" 2 Way active
Power handling:	250W, 500W PEAK	250W, 500W PEAK
LF woofer:	15" with 3" kapton voice coil, 60 OZ magnet	15" with 3" kapton voice coil, 60 OZ magnet
HF driver:	1.75" Titanium	1.75" Titanium
Frequency response:	40Hz-18KHz	40Hz-18KHz
Impedance:	8 Ohm	4 Ohm
Sensitivity:	98dB	98 dB
Amplifier module:		250W RMS Digital AMP
Functions:		Mp3 player, SD card input, Ipod dock, 5 band EQ, FM radio, Remote controller
Connectors:	2*Speakon	Dual RCA line & XLR line input, Dual XLR&1/4JACK MIC input, 1/4Jack MIC input, XLR output
Dimension(W*L*H):	50.5*48*75.5CM	50.5*48*75.5CM
Weight:	21KGS	23KGS

PL Serie

Moulded Speaker Cabinet



PL-8 & PL-8AU

PL-10 & PL-10AU

PL-12 & PL-12AU

PL-15 & PL-15AU

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

Professional Speaker Cabinet

Professional Speaker Cabinet

PR Serie

Moulded Speaker Cabinet



PR-8 & PR-8AU

Model:	PM-8	PM-8AU
System type:	8" 2 Way passive	12" 2 Way active
Power handling:	120W, 240W PEAK	80W, 160W PEAK
LF woofer:	8" with 1.5" kapton voice coil, 30 OZ magnet	8" with 1.5" kapton voice coil, 30 OZ magnet
HF driver:	1" Titanium	1" Titanium
Frequency response:	65Hz-18KHz	65Hz-18KHz
Impedance:	8 Ohm	4 Ohm
Sensitivity:	93dB	93 dB
Amplifier module:		80W RMS , Analog
Functions:		Mp3 player, SD card input, FM radio, Remote controller
Connectors:	2*Speakon	Dual RCA line & 1/4JACK MIC input, Speakon output
Dimension(W*L*H):	31*26*46CM	31*26*46CM
Weight:	8.5KGS	9.5KGS

PR-10 & PR-10AU

Model:	PR-10	PR-10AU
System type:	10" 2 Way passive	10" 2 Way active
Power handling:	150W, 300W PEAK	120W, 240W PEAK
LF woofer:	10" with 2" kapton voice coil, 50 OZ magnet	10" with 2" kapton voice coil, 50 OZ magnet
HF driver:	1.35" Titanium	1.35" Titanium
Frequency response:	55Hz-18KHz	55Hz-18KHz
Impedance:	8 Ohm	4 Ohm
Sensitivity:	95dB	95 dB
Amplifier module:		120W RMS, Analog
Functions:		Mp3 player, SD card input, FM radio, Remote controller
Connectors:	2*Speakon	Dual RCA line & XLR MIC input, XLR&1/4JACK line output, Speakon output
Dimension(W*L*H):	40*35*55CM	40*35*55CM
Weight:	11KGS	12.5KGS

PR-12 & PR-12AU

Model:	PR-12	PR-12AU
System type:	12" 2 Way passive	12" 2 Way active
Power handling:	200W, 400W PEAK	150W, 300W PEAK
LF woofer:	12" with 2.5" kapton voice coil, 50 OZ magnet	12" with 2.5" kapton voice coil, 50 OZ magnet
HF driver:	1.35" Titanium	1.35" Titanium
Frequency response:	50Hz-18KHz	50Hz-18KHz
Impedance:	8 Ohm	4 Ohm
Sensitivity:	95dB	95 dB
Amplifier module:		150W RMS, Analog
Functions:		Mp3 player, SD card input, FM radio, Remote controller
Connectors:	2*Speakon	Dual RCA line & XLR MIC input, XLR&1/4JACK line output, Speakon output
Dimension(W*L*H):	42*37*65CM	42*37*65CM
Weight:	14KGS	16KGS

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

Professional Speaker Cabinet

Professional Speaker Cabinet

PR-15 & PR-15AU

Model:	PR-15	PR-15AU
System type:	15" 2 Way passive	15" 2 Way active
Power handling:	250W, 500W PEAK	180W, 360W PEAK
LF woofer:	15" with 3" kapton voice coil, 60 OZ magnet	15" with 3" kapton voice coil, 60 OZ magnet
HF driver:	1.75" Titanium	1.75" Titanium
Frequency response:	40Hz-18KHz	40Hz-18KHz
Impedance:	8 Ohm	4 Ohm
Sensitivity:	98dB	98 dB
Amplifier module:		180W RMS, Analog
Functions:		Mp3 player, SD card input, FM radio, Remote controller
Connectors:	2*Speakon	Dual RCA line & XLR MIC input, XLR&1/4JACK line output, Speakon output
Dimension(W*L*H):	49*42*76CM	49*42*76CM
Weight:	19KGS	21KGS

PQ Serie

Moulded Speaker Cabinet



PQ-15 & PQ-15AU

Model:	PQ-15	PQ-15AU
System type:	15" 2 Way passive	15" 2 Way active
Power handling:	300W, 600W PEAK	250W, 500W PEAK
LF woofer:	15" with 3" kapton voice coil, 60 OZ magnet	15" with 3" kapton voice coil, 60 OZ magnet
HF driver:	1.75" Titanium	1.75" Titanium
Frequency response:	40Hz-18KHz	40Hz-18KHz
Impedance:	8 Ohm	4 Ohm
Sensitivity:	98dB	98 dB
Amplifier module:		250W RMS, Analog
Functions:		Mp3 player, SD card input, Bluetooth, 5Band EQ, FM radio, Remote controller
Connectors:	2*Speakon	Dual RCA line & XLR MIC input, XLR&1/4JACK line output,
Dimension(W*L*H):	48.5*40*74CM	48.5*40*74CM
Weight:	17KGS	19KGS

PV Serie

Moulded Speaker Cabinet



PY-8 & PY-8AU

PY-10 & PY-10AU

PY-12 & PY-12AU

PY-15 & PY-15AU

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

Professional Speaker Cabinet

Professional Speaker Cabinet

Battery Speaker Cabinet



PP-10AP

Specifications:

10" woofer speaker 2" Kapton voice coil, 40 OZ magnet
1" Silk Film compression driver
MDF Heavy duty wood cabinet

Built in Mp3 player SD card input with LCD display
Built in Bluetooth, FM radio, Rechargeable battery
Built in One VHF wireless Mic

Built in 1/4" Jack Connector for Line input
Built in DC input
Power Handling: 60W
Valid Distance: 35M
Battery consumption: Max volume 2-3 hours, Medium volume 4 hours
Dimension(W*L*H): 43*34*54 CM
Weight: 17KGS

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

Battery Speaker Cabinet



PR-15AWB

Specifications:

15" woofer speaker 2" Kapton voice coil, 40 OZ magnet
1" Titanium compression driver

Built in Mp3 player SD card input with LCD display
Built in Bluetooth, FM radio, ECHO, Rechargeable battery
Built in Two VHF wireless Mic with antenna
Built in 5 Band EQ

Built in XLR Mic input
Built in 1/4" Jack Connector for Line input
Built in RCA Connector for line input & output
Built in DC input
Power Handling: 100W
Valid Distance: 35M
Battery consumption: Max volume 2-3 hours, Medium volume 4 hours
Dimension(W*L*H): 48.5*40*74 CM
Weight: 21KGS

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

Professional Speaker Cabinet

Professional Speaker Cabinet

Battery Speaker Cabinet



PN-12AWB

Specifications:

12" woofer speaker 2" Kapton voice coil, 40 OZ magnet
1" Titanium compression driver

Built in Mp3 player SD card input with LCD display
Built in Bluetooth, FM radio, ECHO, Rechargeable battery
Built in Two VHF wireless Mics with antenna
Built in 5 Band EQ

Built in XLR Mic input
Built in 1/4" Jack Connector for Line input
Built in RCA Connector for line input & output
Built in DC input
Power Handling: 85W
Valid Distance: 35M
Battery consumption: Max volume 2-3 hours, Medium volume 4 hours
Dimension(W*L*H): 42*37*65 CM
Weight: 17KGS

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

Battery Speaker Cabinet



PX-605AWB

Specifications:

6.5" coaxial speaker, 40 OZ magnet
1" kapton voice coil

Built in Mp3 player SD card input with LCD display
Built in Bluetooth, FM radio, ECHO, Rechargeable battery
Built in One VHF wireless Mic
Built in 2 Band EQ

Built in 1/4" Jack Connector for Line input
Built in RCA Connector for line input
Built in DC input
Power Handling: 40W
Valid Distance: 35M
Battery consumption: Max volume 2-3 hours, Medium volume 4 hours
Dimension(W*L*H): 28*21*43 CM
Weight: 8.5KGS

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

Battery Speaker Cabinet



PJ-8AWB

Specifications:

8" woofer speaker 1.5" Kapton voice coil, 30 OZ magnet
1" Titanium compression driver

Built in Mp3 player SD card input with LCD display
Built in Bluetooth, FM radio, ECHO, Rechargeable battery
Built in One VHF wireless Mic, internal signal receiver
Built in 2 Band EQ

Built in 1/4" Jack Connector for Line input
Built in RCA Connector for line input
Built in DC input

Power Handling: 50W

Valid Distance: 35M

Battery consumption: Max volume 2-3 hours, Medium volume 4 hours

Dimension(W*L*H): 32*24*46 CM

Weight: 10.5KGS

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

Battery Speaker Cabinet



PJ-10AWB

Specifications:

10" woofer speaker 1.5" Kapton voice coil, 30 OZ magnet
1" Titanium compression driver

Built in Mp3 player SD card input with LCD display
Built in Bluetooth, FM radio, ECHO, Rechargeable battery
Built in One VHF wireless Mic with effect with antenna
Built in 2 Band EQ
Built in XLR Mic input

Built in 1/4" Jack Connector for Line input

Built in RCA Connector for line input & output

Built in DC input

Power Handling: 70W

Valid Distance: 35M

Battery consumption: Max volume 2-3 hours, Medium volume 4 hours

Dimension(W*L*H): 40*31.5*54 CM

Weight: 13KGS

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

WV Serie

Wooden Speaker Cabinet

Model: **WV-15**
System type: 15" 2 Way
Power handling: 300W, 600W PEAK
LF woofer: 15" with 3" voice coil
HF driver: 1.75" Titanium
Frequency response: 40Hz-20KHz
Impedance: 8 Ohm
Sensitivity: 98dB
Connectors: 2*Speakon & 2*1/4 Jack
Dimension(W*L*H): 53*58*89CM
Weight: 34KGS



WV-15 & WV-215
WV-18S & WV-218S

Model:	WV-215	WV-18S	WV-218S
System type:	Dual 15" 2 Way	18" Subwoofer	Dual 18" Subwoofer
Power handling:	600W, 1200W PEAK	500W, 1000W PEAK	500W, 1000W PEAK
LF woofer:	2*15" with 3" voice coil	18" with 4" voice coil	2*18" with 4" voice coil
HF driver:	1.75" Titanium		
Frequency response:	40Hz-20KHz	38-600Hz	38-600Hz
Impedance:	4 Ohm	8 Ohm	8 Ohm
Sensitivity:	100dB	100 dB	103dB
Connectors:	2*Speakon 2*1/4 Jack	2*Speakon 2*1/4 Jack	2*Speakon 2*1/4 Jack
Dimension(W*L*H):	53*58*130CM	66*58*68CM	66*120*73CM
Weight:	60KGS	45KGS	76KGS

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

WR Serie

Wooden Speaker Cabinet

Model: **WR-12**
System type: 12" 2 Way
Power handling: 250W, 500W PEAK
LF woofer: 12" with 2.5" voice coil
HF driver: 1.35" Titanium
Frequency response: 55Hz-20KHz
Impedance: 8 Ohm
Sensitivity: 96dB
Connectors: 2*Speakon & 2*1/4 Jack
Dimension(W*L*H): 40*39*66CM
Weight: 19.5KGS



WR-12 & WR-15
WR-215 & WR-18S

Model:	WR-15	WR-215	WR-18S
System type:	15" 2 Way	Dual 15" Subwoofer	18" Subwoofer
Power handling:	300W, 600W PEAK	600W, 1200W PEAK	500W, 1000W PEAK
LF woofer:	15" with 3" voice coil	2*15" with 3" voice coil	18" with 4" voice coil
HF driver:	1.75" Titanium	1.75" Titanium	
Frequency response:	45Hz-20KHz	40-20KHz	38-700Hz
Impedance:	8 Ohm	4 Ohm	8 Ohm
Sensitivity:	98dB	99 dB	100dB
Connectors:	2*Speakon 2*1/4 Jack	2*Speakon 2*1/4 Jack	2*Speakon 2*1/4 Jack
Dimension(W*L*H):	45*48*86CM	45*48*132CM	66*58*73CM
Weight:	25KGS	42KGS	45KGS

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

Professional Speaker Cabinet

Professional Speaker Cabinet

WQ Serie

Wooden Speaker Cabinet

Model: **WQ-12**
 System type: 12" 2 Way
 Power handling: 250W,500W PEAK
 LF woofer: 12"with 2.5" voice coil
 HF driver: 1.35"Titanium
 Frequency response:55Hz-20KHz
 Impedance: 8 Ohm
 Sensitivity: 96dB
 Connecors: 2*Speakon & 2*1/4 Jack
 Dimension(W*L*H): 38*37*65CM
 Weight: 19KGS



WQ-12 & WQ-15
 WQ-215 & WQ-18S

Model:	WQ-15	WQ-215	WQ-18S
System type:	15" 2 Way	Dual 15" 2 Way	18" Subwoofer
Power handling:	300W,600W PEAK	600W,1200W PEAK	500W,1000W PEAK
LF woofer:	15"with 3"voice coil	2*15" with 3"voice coil	18" with 4"voice coil
HF driver:	1.75"Titanium	1.75"Titanium	
Frequency response:	45Hz-20KHz	40-20KHz	38-650Hz
Impedance:	8 Ohm	4 Ohm	8 Ohm
Sensitivity:	98dB	99 dB	100dB
Connecors:	2*Speakon 2*1/4 Jack	2*Speakon 2*1/4 Jack	2*Speakon 2*1/4 Jack
Dimension(W*L*H):	43*46*85CM	43*46*130CM	56*58*68CM
Weight:	24KGS	38KGS	36KGS

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

WJ Serie

Model:	WJ-12M	WJ-15
System type:	12" 2 Way monitor	15" 2 Way
Power handling:	300W,600W PEAK	400W,800W PEAK
LF woofer:	12"with 3" voice coil	15"with 4" voice coil
HF driver:	1.75"Titanium	1.75"Titanium
Frequency response:	45Hz-20KHz	40Hz-20KHz
Impedance:	8 Ohm	8 Ohm
Sensitivity:	97dB	99dB
Connecors:	2*Speakon & 2*1/4 Jack	2*Speakon & 2*1/4 Jack
Dimension(W*L*H):	37*33*59CM	46*45*78CM
Weight:	19KGS	

Wooden Speaker Cabinet

WQ-12 & WQ-15
 WQ-215 & WQ-18S



Model:	WJ-215	WJ-18S	WJ-218S
System type:	Dual 15" 2 Way	15" Subwoofer	Dual 18" Subwoofer
Power handling:	600W,1200W PEAK	600W,1000W PEAK	1200W,2500W PEAK
LF woofer:	2*15"with 4"voice coil	18" with4"voice coil	2*18" with 4"voice coil
HF driver:	2"Titanium		
Frequency response:	40Hz-20KHz	38-700Hz	38-700Hz
Impedance:	4 Ohm	8 Ohm	8 Ohm
Sensitivity:	101dB	102 dB	103dB
Connecors:	2*Speakon 2*1/4 Jack	2*Speakon 2*1/4 Jack	2*Speakon 2*1/4 Jack
Dimension(W*L*H):	56*54*130CM	63*53*67CM	66*122*73CM
Weight:	42KGS	34KGS	77KGS

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

Professional Speaker Cabinet

Professional Speaker Cabinet

COMBO PA SYSTEM



PPA-10J

Specifications:

2 Way combo pa system with Class-D power mixer with Mp3 player,
 SD card input LCD display,remote control
 2" 150W output,4 Ohm
 LF Woofer speaker: 10" with 2" Kapton voice coil

Sensitivity: 96dB
 Frequency response: 55-20KHz
 4 Channel power mixer with switch power supply
 4 Channel XLR Mic input

Stereo RCA & 1/4Jack Line input
 Output: 2*1/4Jack
 2 Band EQ,Treble & Bass on each channel
 Dimension(W*L*H): 63.5*36*54 CM
 Weight: 22KGS

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

COMBO PA SYSTEM



PPA-18152

Specifications:

3 Channel integrated pa system with active subwoofer with Mp3 player,
 SD card input,Bluetooth
 Active subwoofer: 600W RMS,1200W PEAK
 LF Woofer speaker: 15" with 2.5" Kapton voice coil
 Satellite speaker: 2*200W
 Frequency response: 35-20KHz
 2*Dual RCA & 2*Canon input 2*Speaker input
 2*Speakon output

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

Woofers Speaker

Woofers Speaker

SW-001



Model:	SW-00108	SW-00110	SW-00112	SW-00115
Size:	8" Woofer	10" Woofer	12" Woofer	15" Woofer
Magnet:	30 oz	40 oz	70 oz	80 oz
Frequency:	52Hz-6KHz	52Hz-6KHz	42Hz-5KHz	35Hz-3KHz
Voice Coil:	1.5"KSV	2"KSV	3"KSV	3"KSV
Impedance:	8 Ohm	8 Ohm	8 Ohm	8 Ohm
SPL:	91 db/W/M	94 db/W/M	97 db/W/M	98 db/W/M
Power:	180 W	250W	300W	400W

SW-002



Model:	SW-00212	SW-00215
Size:	12" Woofer	15" Woofer
Magnet:	50 oz	70 oz
Frequency:	42Hz-5KHz	35Hz-3KHz
Voice Coil:	2.5"KSV	3"KSV
Impedance:	8 Ohm	8 Ohm
SPL:	94 db/W/M	96 db/W/M
Power:	200 W	300W

SW-004



Model:	SW-00412	SW-00415
Size:	12" Woofer	15" Woofer
Magnet:	Neo 65 oz	Neo 75 oz
Frequency:	42Hz-5KHz	35Hz-3KHz
Voice Coil:	2.5"KSV	3"KSV
Impedance:	8 Ohm	8 Ohm
SPL:	97 db/W/M	98 db/W/M
Power:	400 W	600W

Woofers Speaker

Woofers Speaker

SW-006

Model:	SW-00615	SW-00618
Size:	15" Woofer	18" Woofer
Magnet:	80 oz	100 oz
Frequency:	30Hz-2.5KHz	34Hz-3KHz
Voice Coil:	3"KSV	4"KSV
Impedance:	8 Ohm	8 Ohm
SPL:	97 db/W/M	98 db/W/M
Power:	400 W	600W



SW-007



Model:	SW-00712	SW-00715	SW-00718
Size:	12" Woofer	15" Woofer	18" Woofer
Magnet:	60 oz	80 oz	100 oz
Frequency:	52Hz-2KHz	30Hz-2.5KHz	34Hz-3KHz
Voice Coil:	2.5"KSV	3"KSV	4"KSV
Impedance:	8 Ohm	8 Ohm	8 Ohm
SPL:	94 db/W/M	97 db/W/M	98 db/W/M
Power:	300 W	400W	600W

SW-008



Model:	SW-00812	SW-00815
Size:	12" Woofer	15" Woofer
Magnet:	100 oz	100 oz
Frequency:	50Hz-2KHz	30Hz-2.5KHz
Voice Coil:	4"KSV	4"KSV
Impedance:	8 Ohm	8 Ohm
SPL:	98 db/W/M	99 db/W/M
Power:	400 W	600W

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

Compression Driver

Compression Driver

DC-003



Specifications:
 Impedance: 8Ω
 Power: 35W
 Sensitivity(1W/1M): 110dB
 Frequency Range: 1.2-20KHz
 Voice Coil: 34.4mm
 Magnet: 13 oz
 Diaphragm: Titanium

DC-005



Specifications:
 Impedance: 8Ω
 Power: 35W
 Sensitivity(1W/1M): 110dB
 Frequency Range: 1.2-20KHz
 Voice Coil: 34.4mm
 Magnet: 13 oz
 Diaphragm: Titanium

DC-007



Specifications:
 Impedance: 8Ω
 Power: 50W
 Sensitivity(1W/1M): 110dB
 Frequency Range: 1.2-20KHz
 Voice Coil: 44.4mm
 Magnet: 22.6 oz
 Diaphragm: Titanium

DC-009



Specifications:
 Impedance: 8Ω
 Power: 85W
 Sensitivity(1W/1M): 110dB
 Frequency Range: 1-20KHz
 Voice Coil: 51.3mm
 Magnet: 33 oz
 Diaphragm: Titanium

DC-010



Specifications:
 Impedance: 8Ω
 Power: 85W
 Sensitivity(1W/1M): 110dB
 Frequency Range: 1-20KHz
 Voice Coil: 51.3mm
 Magnet: 33 oz
 Diaphragm: Titanium

DC-011



Specifications:
 Impedance: 8Ω
 Power: 130W
 Sensitivity(1W/1M): 105dB
 Frequency Range: 600-18KHz
 Voice Coil: 72.5mm
 Magnet: 57.5 oz
 Diaphragm: Titanium

[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

DI BOX

DI BOX

DIRECT

Specifications:

PASSIVE
 Frequency Response 10Hz-25KHz
 Noise Level(22Hz-22KHz, Input Shorted) -100dBu
 THD + N(10Hz-22KHz) 0.01% typ. @1V RMS,
 1KHz input
 One 1/4" Phone Jack, Unbalanced
 XLR connector (Balanced or Unbalanced)
 Output One XLR connector, Balanced
 Line Output One 1/4" Phone Jack, Unbalanced
 PAD Switch 0dB, -20dB, -40dB setting
 Dimensions 158 x 100 x 50mm
 Weight 0.4kg



DI PLUS

Specifications:

Frequency Response 10Hz-25KHz
 Noise Level(22Hz-22KHz, Input Shorted) -100dBu
 THD + N(10Hz-22KHz) 0.01% typ. @1V RMS, 1KHz
 Input Two 1/4" Phone Jack, Unbalanced
 Output Two XLR connector, Balanced
 Line Output Two 1/4" Phone Jack, Unbalanced
 PAD Switch 0dB, -20dB, -40dB setting/
 Two switches
 LIFT Switched Two Ground LIFT Switches
 Dimensions 158 x 100 x 50mm
 Weight 0.4kg



[Http://www.hukeelectronics.com](http://www.hukeelectronics.com)

DI BOX

MIX-5

Specifications:

5 CH MINI MIXER
 Frequency Response 20Hz-20KHz
 Noise Level(22Hz-22KHz,Input Shorted)-900dBu
 THD + N(10Hz-22KHz)0.013%typ.@1V
 1KHz Max input Level for Unbalanced
 Input(1% THD)-14dBu Input
 Two 1/4"Phone Jack,Unbalanced
 One XLR connector,Balanced
 Stereo RCA Jack,Unbalanced
 Output One 1/4"Phone Jack,Unbalanced
 Stereo RCA Jack,Unbalanced
 Dimensions 158 x 100 x 50mm
 Weight 0.4kg



DI BOX

PHANTOM

Specifications:

Frequency Response 10Hz-20KHz
 Noise Level(22Hz-22KHz,Input Shorted)-100dBu
 THD + N(10Hz-22KHz)0.013%typ.@1V RMS,
 1KHz input
 Two XLR connector,Balanced
 Output Two XLR connectors,Balanced
 Phantom Power
 Select Switch 12V/48V
 Dimensions 158 x 100 x 50mm
 Weight 0.4kg



HOT DIRECT

Specifications:

ACTIVE
 Frequency Response 20Hz-20KHz
 Noise Level(22Hz-22KHz,Input Shorted)-100dBu
 THD + N(10Hz-22KHz)0.01%typ.@1V RMS,1KHz
 Max.Input Level(1%THD) + 6dBu
 Input One 1/4"Phone Jack,Unbalanced
 XLR connector(Balanced or Unbalanced)
 Output One XLR connector,Balanced
 Line Output One 1/4"Phone Jack,Unbalanced
 PAD Switch 0dB, -20dB, -40dB setting
 LIFT Switched Ground LIFT Switches
 Dimensions 158 x 100 x 50mm
 Weight 0.4kg

